

Podatkovni list izdelka: HSED02UB2F

Doza, TOOLLESS LINE Outlet, za 2 modula, 80x80mm, RAL1013



Tehnični podatki

SCHRACK format	SFA in SFB
montaža	nadometna kabelski kanal talna doza podometna
število vhodov	2
barva	RAL 1013
stopnja mehanske zaščite	IP20
neto masa (kg)	0,08
min. temperatura okolja (°C)	-10
maks. temperatura okolja (°C)	60

Tabela izdelkov

Opis	Šifra
Doza, TOOLLESS LINE Outlet, za 2 modula, 80x80mm, RAL1013	HSED02UB2F
dodatni pribor	
Modul RJ45, TOOLLESS LINE, oklopljen, Cat.6a 10GB 4PPoE 100W AMD2	HSEMRJ6GWA
Modul, RJ45, TOOLLESS LINE, oklopljen, razred Ea 10GB 4PPoE 100 W (SFA)	HSEMRJ6GWT
Modul RJ45, TOOLLESS LINE, oklopljen, Cat.6 (SFA)	HSEMRJ6GWS
Modul, RJ45, TOOLLESS LINE, oklopljen, Cat. 5e, (SFA)	HSEMRJ5GWS
Modul, RJ45, TOOLLESS LINE, okloplj.,Cat.6a, 10GB 4PPoE 100W (SFB)	HSEMRJ6GBA
Modul, RJ45, TOOLLESS LINE, oklopljen, Cat.6, SFB	HSEMRJ6GBS
Modul RJ45, TOOLLESS LINE, neoklopljen, Cat.6, (SFA)	HSEMRJ6UWS
Modul, RJ45, TOOLLESS LINE, neoklopljen, Cat. 5e, (SFA)	HSEMRJ5UWS
Vmesnik, RJ45 oklopljen, razred Ea 10GB (SFA)	HSEMRKRGWS
Vmesnik, koaksialni, F-ženski na F-ženski konektor (SFA)	HSEMRKFFWS
Modul, prazen, TOOLLESS LINE, LWL, za LC-Duplex/SC-Simplex	HSEMRLLLWS