

Podatkovni list izdelka: HVSMRJ5UWS

Vtičnica RJ45 neoklopljena kat.5e (SFA)



SCHRACK-Info

TRANSMISSION PERFORMANCE

- Meet all requirements specified in connecting hardware requirement of ANSI/TIA-568-C.2, Category 5e

ELECTRICAL

- Electrical Insulation Resistance: 500MΩ min. 100VDC
- Dielectric Withstanding Voltage : 1000VDC or a.c. Peak Contact to Contact 60Hz for 1 minute

MECHANICAL

- Insertion / Extraction Life: 750 Cycles Minimum
- IDC Wire Gauge: 22 ~ 24 AWG

PHYSICAL

- Housing: High-Impact, Flame-Retardant Plastic, UL 94V-0
- Spring Wire: Phosphor Bronze Alloy Plated with 50μ-inch of Gold
- IDC: Phosphor Bronze Alloy with 100μ-inch 100% Sn Alloy



Tehnični podatki

Neto širina (mm)	16,90
Neto višina (mm)	21,90

Tehnični podatki - Nadaljevanje

Min. temperatura okolice (°C)	-10
Maks. temperatura okolice (°C)	60

Tabela izdelkov

Opis	NVP (%)	Teža bakra (kg/km)	Šifra
Vtičnica RJ45 neoklopljena kat.5e (SFA)			HVSMRJ5UWS
Dodatna oprema			
Orodje za krimpanje za HVSMRJ5UWS / HVSMRJ6UWS			HVSTOOL01S
Kabel U/UTP, Cat.5e, 4x2xAWG24/1, PVC Eca moder, karton 305m karton 305m	69	15	HSEKU424P1
Kabel U/UTP, Cat.5e, 4x2xAWG24/1, PVC, Eca, siv, karton 305m karton 305m	69	15	HSEKU424P0
Kabel U/UTP Cat.5e, 4x2xAWG24/1, LS0H Eca moder, karton 305m karton 305m	69	15	HSEKU424H1
Plošča, spajalna, 19", prazna, za 24 modulov (SFA/SFB), 1 HE svetlo siva RAL7035, pritrditev spajalnih kablov spodaj			HSER0240GS
Adapter za DIN-letev, prazen, za 1 modul (SFA/SFB) svetlo siv			HSERH010GS
Vtičnica, podatkovna, prazna, 80x80mm, za 1 modul (SFA/SFB) poševna, RAL9010 bela			HSED01UW2S
Vtičnica, podatkovna, 80x80mm, prazna, za 2 modula (SFA/SFB) poševna, RAL9010 bela			HSED02UW2S