

Podatkovni list izdelka: IG713708-A

Okvir nadometni s hrbtnosteno za števčno priključno ploščo

za IL900070-B, vključno 5 x 80mm TX25 pocinkano jeklo okrogla glava Torx vijaki in imbus ključ za TX25



Tehnični podatki

neto širina (mm)	210,00
neto višina (mm)	370,00
neto globina (mm)	39,00
neto masa (kg)	0,50
EAN-koda	9120075475037
toplotne izgube (W)	-10,00
min. temperatura okolja (°C)	-25
maks. temperatura okolja (°C)	65

Tabela izdelkov

Opis	Šifra
Okvir nadometni s hrbtnosteno za števeno priključno ploščo za IL900070-B, vključno 5 x 80mm TX25 pocinkano jeklo okrogla glava Torx vijaki in imbus ključ za TX25	IG713708-A
dodatni pribor	
Kontakti 6/5 44mm za števec	IL900309
Plug-in counter bar 50A for Vienna, Tyrol and Styria Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm ² , flexible with crimped ferrule, Material Terminal Inserts from coated Copper, RoHS konform, OVE R21:2019	IL900189
Plug-in counter bar Netz NÖ 63 A, 3-pole+2N, 6-25 mm ² without tariff connection	IL900169-A
Plug-in counter bar 80A, 3-pole+1N for VKW, Wiener Netze 6-35mm ² , without tariff connection	IL900188-A
Plug-in counter bar pins 63A, 44mm, PU=7 pieces	IL900190
Cover for Plug-in counter bars for Plug-in counter Terminals IL900189-- The release handle is used to release the springs in the meter terminal, allowing the meter to be inserted or removed. Made of robust IL90029E polyamide.	IL900191
Plug-in counter bar 63A, 1-pole+2N, Salzburg AG, Wiener Netze 6-25mm ² , with tariff connection	IL900478
Sponka, števnica, 80A 3p+1N za KNG, Salzburg AG, omrežje Bgld 6-35mm ² , brez tarifnega priključka	IL900555-A
4-polige Zähleranschlussklemme EVN, 50A, 10-16mm ² , grün	IL900196
4-polige Zähleranschlussklemme Wiener Netze grün	IL900496
Plug-in counter bar ADOCK 1-pole + 2N	IL900282
Plug-in counter bar ADOCK 3-pole + 2N Connection at bottom or back	IL900284
Meter connecon terminal 1P+2N, for Tyrol and Styria Connection at bottom	IL900350
Cover for connection terminal 1P+2N, for Styria and Tyrol für Steiermark und Tirol	IL900351
Meter connecon terminal 3P+2N, for Tyrol and Styria Connection at bottom	IL900352
Cover for connection terminal 3P+2N, for Tyrol and Styria für Steiermark und Tirol	IL900353
ADOCK terminal cover for 3-phase power meter IL900352 max. 60A, according to DIN 43857	IL900357
Cover for ADOCK connection terminal 1P+2N, Upper Austria for IL900282	IL900560

Tabela izdelkov

Opis	Šifra
dodatni pribor	
Cover for ADOCK connection terminals 3P+2N, Upper Austria for IL900284, IL900285, IL900286, IL900287, IL900289	IL900561
Plošča, števnica, siva, s pritrditvijo iz umetne mase, tip B izdelano in preizkušeno v skladu z OVE E 8640:2022, IP20, material polikarbonat in ABS, negorljivo, brez halogenov, trdnost žarilne žice 650°C, smernica RoHS III 2015/863/EU	IL900070-B