

Podatkovni list izdelka: ILT30800-A

Polje, odvodno, NV, 822mm, 800A, 50x10 bakreni sistem



SCHRACK-Info

- **General** : Type-tested Modul 2000TT outgoing fields for HRC in-line fuse switches up to 630A
- **Material** :
 - Corpus: 1.5mm galvanised sheet steel
 - Doors: Single door and double door: 1.5mm sheet steel
- **Door** :
 - Made of sheet steel and equipped with M8 threaded bolts for earthing. Enclosures in widths 602mm and 822mm are single door versions, enclosures in widths 1042mm and 1242mm are double door versions
 - On single door enclosures, the door is mounted on three double-sided hinges for right-hand opening (=hinged right). On double door enclosures, hinges are not reversible, the left door wing is locked separately with an inner three-point lock
- **Lock** : Three-point rod lock with swing handle (without lock insert), does not slide inward. The standard lock can be exchanged for profile half cylinders (DIN cylinders) from the range of accessories. Double doors are designed with a left-side inner pivot lever
- **Roof** :
 - Two cut-outs for cable entries at widths 602mm and 822mm, three cut-outs at width 1042mm and four cut-outs at width 1242mm
 - Gland plates from our accessories are required for completion
- **Side cut-out** : Contacting possibility for the main busbar. 1 PU (=2 pieces) side covers **IL920001** per enclosure is necessary
- **Baying kit** : A baying kit for baying a second Modul 2000TT enclosure is included
- **Plinth** : 100mm high with cable entry options on the sides. Optionally it is possible to stack two 100mm high plinths on top of each other

- **Protection class** : I
- **Degree of protection** : Standard IP31 up to 1250A, without door it's possible up to 1600A, with corresponding components from our accessories (exhaust filter, gland plates and plinths) IP54 is possible up to 1250A
- **Impact resistance** : IK10
- **Finish** : Textured powder coating
- **Color** : RAL 7035 (Light grey)
- **Delivery includes** :
 - Enclosure with plinth
 - Door with earthing studs
 - Main busbar system
 - Transparent polycarbonate covers
 - Transport connection for main busbar system
 - Baying kit for one more enclosure

Delivered on an Euro-pallet



Tehnični podatki

neto širina (mm)	822,00
neto višina (mm)	2.140,00
neto globina (mm)	400,00
neto masa (kg)	190,00
min. temperatura okolja (°C)	-5
maks. temperatura okolja (°C)	40
stopnja mehanske zaščite	IP31
material	jeklena pločevina
barva	RAL 7035
širina (mm)	822
višina (mm)	2138
globina (mm)	400
toplotne izgube (W)	-859,00
ŠxVxG mm	822x2140x400
EAN-koda	9004840837247

Opis	Teža bakra (kg/km)	Šifra
Polje, odvodno, NV, 822mm, 800A, 50x10 bakreni sistem		ILT30800-A

potrebna oprema

Tabela izdelkov

Opis	Teža bakra (kg/km)	Šifra
potrebna oprema		
Stranica s prirobnico, za Modul 2000TT (EE=2 kosa)		IL920001
Prirobnica, izolacijska (slepa), IP66		IL958001-A
Prirobnica, izolacijska, IP55, 9xØ3-20, 1xØ3-40, 2xØ3-70mm penasta guma		IL958007-A
Prirobnica, izolacijska, IP66, 4xM16, 6xM25/16, 8xM32/20		IL958002-A
Prirobnica, izolacijska, 2xM20, 8xM25/16, 4xM32/20, 1xM50/32 IP66		IL958003-A
Prirobnica izolacij. IP66 2xM16, 12xM20, 2xM40/25, 2xM50/32 IP66		IL958004-A
Prirobnica, izolacijska, IP66, 24xM16, 13xM20		IL958005-A
Prirobnica, izolacijska, IP55, 44xØ3-14, 3xØ3-21, 2xØ3-30mm penasta guma		IL958006-A
dodatni pribor		
Vložek, inštalacijski, 3-42K komplet, jeklena pločevina, NH za NV-varovalčne letve		ILTAK342
NV-varovalčna letev ARROW LINE vel. 00, 3-p., sistem 100 mm za 100 mm zbiralni sistem, M8	420	ISA05261
Adapter, dvojni, 100/185mm, velikost 00 serija ARROW II	469	ISA05326
Prekritje za ARROW II letev 00 (1 set = 2 kosa) izravnalne plošče za prilagoditev višine prekritja velikosti 1-3		ISA05329
NV-varovalčna letev ARROW LINE vel.1, 250A, 3-pol., M10 NH-Leiste	1943	ISA05305
NV-varovalčna letev ARROW LINE vel.2, 400A, 3-pol., M12 za 185mm zbiralni sistem	1952	ISA05311
NV-varovalčna letev ARROW LINE vel.3, 630A, 3-pol., M12 za 185mm zbiralni sistem	2662	ISA05320
NV-varovalčna letev ARROW LINE vel.1, 250A, 3-pol., V-sponka za 185mm zbiralni sistem	1965	ISA05306
NV-varovalčna letev ARROW LINE vel.2, 400A, 3-pol., V-sponka za 185mm zbiralni sistem	1965	ISA05312
NV-varovalčna letev ARROW LINE vel.3, 630A, 3-p., V-sponka za 185mm zbiralni sistem	2685	ISA05321
NV-varovalčna letev ARROW II, vel.00, 3-pol. za tokovnik, M8 izvedba za integracijo tokovnika, za 100 mm zbiralni sestav	391	ISA05340
NV-varovalčna letev ARROW II, vel.1, 3-pol. za tokovnik, M12 izvedba za integracijo tokovnika, za 185 mm zbiralni sestav	1948	ISA05341

Tabela izdelkov

Opis	Teža bakra (kg/km)	Šifra
dodatni pribor		
NV-varovalčna lettev ARROW II, vel.2, 3-pol. za tokovnik, M12 izvedba za integracijo tokovnika, za 185 mm zbiralčni sestav	1948	ISA05342
NV-varovalčna lettev ARROW-LINE, vel.3, 3-pol. za tokovnik izvedba za integracijo tokovnika, za 185 mm zbiralčni sestav	2633	ISA05343
Pokrov za ARROW II lettev 1–3, namestitvev zgoraj/spodaj		ISA05334
Prekritje praznega prostora 50mm za ARROW II Line NV-letve za prekritje že pripravljenih izrezov za NV-letve ARROW II v 185mm zbiralčnem sistemu		ISA05356
Prekritje praznega prostora 100mm za NV-letve vel. 1–3 za prekritje že pripravljenih izrezov za NV-letve ARROW II v 185mm zbiralčnem sestavu		ISA05357
Polcilindrični vložek za ključ z dvojno brado 5mm		IU001906
Filter izhodni 252x252x38mm, IP54 za IUKNF4523A, IUKNF5523A		IUKNE450
Podstavek, širinski del, 3A, perforiran		IL957300
Podstavek, globinski del 400mm, s kabelsko uvodnico, V=100mm 1 par, vključno z vijaki, izrez 290x50mm		IL090140
Plošča, prekrivna, 3B18, jeklena pločevina z izrezom za NV-varovalčne letve		ILT56318-A
Pedal za načrte, A4, samolepilni ali pritrditev z vijaki		ASDRA400
Vijak, pocinkan, očesni, M12 za dvigovanje omar AC in KC EE=4 kos		ACLE9301
Plošča, prekrivna, za plombiranje, 2 kosa + 4 klini ni je mogoče odstraniti s sprednje strani		IL900112-F