

Podatkovni list izdelka: LID13784--

7835W/D LED trak 24V DC DL 5m zvitek

14,4W/m IP68

LED trak, zatemnilni, zvitek 5 metrov; 08 STRIPS & PROFILES



Informacija o izdelku

Waterproof flexible LED light strip, with SMD2835 LEDs, 70LEDs/meter, 14,4W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing, IP68. Can be cut every 10cm (7-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.

Tehnični podatki

barva svetlobe	hladno bela
barvna temperatura (K)	6000
indeks barvnega videza Ra	≥90
zatemnilno	odvisno od napajalnika da
zaščitni razred	III
stopnja mehanske zaščite	IP68
EEK	F
razred energetske učinkovitosti	F
vrsta svetilke	LED trak
vklij. s svetlobnim virom	da
okov	LED Platine

Tehnični podatki - Nadaljevanje

sistemska učinkovitost (lm/W)	81
krmilna naprava	potrebno naročiti posebej
delovna napetost DC (V)	24
vhodna napetost DC (V)	24
montaža	talna nadgradna stenska nadgradna nadgradna stropna
material	silikon
dolžina (mm)	5000
širina (mm)	10
dodatni pribor	LID16631--
svetlobni tok/m (lm/m) (lm/m)	1170

Tabela izdelkov

Opis	Šifra
7835W/D LED trak 24V DC DL 5m zvitek 14,4W/m IP68 LED trak, zatemnilni, zvitek 5 metrov; 08 STRIPS & PROFILES	LID13784
dodatni pribor	
7827A montažna sponka za 7830W/RGBW, 7846W, 7846WA 14mm 08 STRIPS & PROFILES	LID16631