

Podatkovni list izdelka: LID13852--

Sutil Round2 LED 18W, 3000K, 1080lm, 120°, IP40, siva **€ECONOMY**

LED vgradni panel



Informacija o izdelku

18W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms. Supplied with 450mA non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.



Tehnični podatki

svetlobni tok (lm) (lm)	1080
barva svetlobe	toplo bela
barvna temperatura (K)	3000
indeks barvnega videza Ra	≥80
življenjska doba	30.000h
zatemnilno	ne
zaščitni razred	II
stopnja mehanske zaščite	IP40
vrsta svetilke	LED panel
vklj. s svetlobnim virom	da

Tehnični podatki - Nadaljevanje

število svetilk	1
okov	LED Platine
kot osvetlitve (°)	120
sistemska učinkovitost (lm/W)	60
faktor moči	0,9
moč (W)	18
krmilna naprava	LED napajalnik
delovna napetost AC (V)	220-240
vhodna napetost AC (V)	220-240
delovni tok mA (mA)	450
frekvenca (Hz)	50/60
montaža	podometna vgradna
izrez (mm)	Ø 210
vgradna globina (mm)	50
barva	siva
material	akril tlačno liti aluminij
višina (mm)	22
premer (mm)	223
dodatni pribor	LID16598--
ØxV mm	223x22
IZREZ (mm)	Ø 210

Merska skica: Sutil Round2 LED 18W, 3000K, 1080lm, 120°, IP40, siva




Tabela izdelkov

Opis	Šifra
Sutil Round2 LED 18W, 3000K, 1080lm, 120°, IP40, siva LED vgradni panel	LID13852
dodatni pribor	
89050TLD DALI/PUSH TO DIM/ 1-10V /TRIAC univ. napajalnik 50W IP20 230V; 23 DRIVERS	LID16598