

Podatkovni list izdelka: LID14466--

7835C/W trak CRI97 24V DC WW 5m zvitek

14,4W/m IP20

LED trak, zatemnilni, zvitek 5 metrov; 08 STRIPS & PROFILES



Informacija o izdelku

Full Spectrum CRI97 Flexible LED light strip, with SMD2835 LEDs, 70LEDs/meter, 14,4W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing. Can be cut every 10cm (7-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.

Tehnični podatki

barva svetlobe	toplo bela
barvna temperatura (K)	3000
indeks barvnega videza Ra	≥97
zatemnilno	odvisno od napajalnika da
zaščitni razred	III
stopnja mehanske zaščite	IP20
EEK	F
razred energetske učinkovitosti	E
vrsta svetilke	LED trak
vklij. s svetlobnim virom	da
okov	LED Platine

Tehnični podatki - Nadaljevanje

sistemska učinkovitost (lm/W)	105
krmilna naprava	potrebno naročiti posebej
delovna napetost DC (V)	24
vhodna napetost DC (V)	24
montaža	talna nadgradna stenska nadgradna nadgradna stropna
dolžina (mm)	5000
dodatni pribor	LID 14125--
svetlobni tok/m (lm/m) (lm/m)	1512

Tabela izdelkov

Opis	Šifra
7835C/W trak CRI97 24V DC WW 5m zvitek 14,4W/m IP20 LED trak, zatemnilni, zvitek 5 metrov; 08 STRIPS & PROFILES	LID14466
dodatni pribor	
7835P LED kabel napajalni za 7825/7835/7835C/7870 10mm 08 STRIPS & PROFILES	LID14125