


Podatkovni list izdelka: LID15113--

38236M/C IP65 LED 60W CW 230V PC/PC

IK08, svetilka za vlažne prostore, z napajalnikom; 21 INDUSTRIAL & FLDS



Krivulja svetlobne porazdelitve



Informacija o izdelku

IP65 LED fitting to replace T8 IP65 traditional waterproof fluorescent. Stainless steel clips included. Polycarbonate body and diffuser. Supplied with non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.

Tehnični podatki

svetlobni tok (lm) (lm)	6000
barva svetlobe	nevtralno bela
barvna temperatura (K)	4000
indeks barvnega videza Ra	≥80
življenjska doba	30.000h
zatemnilno	ne

Tehnični podatki - Nadaljevanje

zaščitni razred	I
stopnja mehanske zaščite	IP65
mehanska odpornost	IK08
vrsta svetilke	vodotesne svetilke
vklij. s svetlobnim virom	da
okov	LED Platine
sistemska učinkovitost (lm/W)	100
faktor moči	0,9
moč (W)	60
krmilna naprava	LED napajalnik
delovna napetost AC (V)	220-240
vhodna napetost AC (V)	220-240
delovni tok mA (mA)	1450
vhodni tok (A)	1,45
frekvenca (Hz)	50/60
montaža	stenska nadgradna nadgradna stropna
barva	siva
material	PC
prekritje	opalno
dolžina (mm)	1215
širina (mm)	113
višina (mm)	80
dodatni pribor	LID16949--
DxŠxV mm	1215x113x80

Merska skica: 38236M/C IP65 LED 60W CW 230V PC/PC



Tabela izdelkov

Opis	Šifra
38236M/C IP65 LED 60W CW 230V PC/PC IK08, svetilka za vlažne prostore, z napajalnikom; 21 INDUSTRIAL & FLDS	LID15113
dodatni pribor	
050180E konektor hitri priklop kablov 32A 2x3-port 26 ACCES&GADGETS	LID16949