

Podatkovni list izdelka: LID15526--

7820V/C LED trak 24VDC CW 5m zvitek

4,8W/m vertikalni

potreben 24V DC napajalnik; 08 STRIPS & PROFILES



Informacija o izdelku

Vertical light Flexible LED light strip, with SMD3014 LEDs, 60LEDs/meter, 4,8W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing. Can be cut every 10cm (6-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.

Tehnični podatki

barva svetlobe	nevtrarno bela
barvna temperatura (K)	4000
indeks barvnega videza Ra	≥90
zatemnilno	odvisno od napajalnika da
zaščitni razred	III
stopnja mehanske zaščite	IP20
vrsta svetilke	LED trak
vklij. s svetlobnim virom	da
okov	LED Platine
sistemska učinkovitost (lm/W)	104
krmilna naprava	potrebno naročiti posebej

Tehnični podatki - Nadaljevanje

delovna napetost DC (V)	24
vhodna napetost DC (V)	24
montaža	talna nadgradna stenska nadgradna nadgradna stropna
dodatni pribor	LID12346--; LID12344--;
svetlobni tok/m (lm/m) (lm/m)	500

Merska skica: 7820V/C LED trak 24VDC CW 5m zvitek 4,8W/m vertikalni

Cut every 10cm
(6-LED segment)



Tabela izdelkov

Opis	Šifra
7820V/C LED trak 24VDC CW 5m zvitek 4,8W/m vertikalni potreben 24V DC napajalnik; 08 STRIPS & PROFILES	LID15526
dodatni pribor	
7824 kabel napajalni za 7820/7829/7829A/7820V/7835V 8mm za 7820/7829/7829A/7820V/7835V, 08 STRIPS & PROFILES	LID12346
7822 LED trak konektor za 7820/7829/7829A/7820V/7835V 8mm 08 STRIPS & PROFILES	LID12344