

Podatkovni list izdelka: LID16853--

7884/W dvojni LED trak 24V WW 5m zvitek

33W/m IP20

08 STRIPS & PROFILES



Informacija o izdelku

Flexible LED light strip, with SMD2835 320 LEDs/m, 33W/m. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing. Can be cut every 2,5cm (8-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.

Tehnični podatki

barva svetlobe	toplo bela
barvna temperatura (K)	3000
indeks barvnega videza Ra	≥90
zatemnilno	odvisno od napajalnika da
zaščitni razred	III
stopnja mehanske zaščite	IP20
EEK	E
razred energetske učinkovitosti	E
vrsta svetilke	LED trak
vklij. s svetlobnim virom	da
okov	LED Platine

Tehnični podatki - Nadaljevanje

kot zaznavanja (°)	
sistemska učinkovitost (lm/W)	124
krmilna naprava	potrebno naročiti posebej
delovna napetost DC (V)	24
vhodna napetost DC (V)	24
montaža	talna nadgradna stenska nadgradna nadgradna stropna
širina (mm)	30
dodatni pribor	LID16949--
svetlobni tok/m (lm/m) (lm/m)	4100

Tabela izdelkov

Opis	Šifra
7884/W dvojni LED trak 24V WW 5m zvitek 33W/m IP20 08 STRIPS & PROFILES	LID16853
dodatni pribor	
050180E konektor hitri priklop kablov 32A 2x3-port 26 ACCES&GADGETS	LID16949