

Podatkovni list izdelka: LID17788--

38150BU/W/V bel 48x reflektor 40W 34° UGR17+UPLIGHT 20W 120°

direktna (20/30/40W) 34° / indirektna (16/20/25W) 120°, 3m kablaj; CCTV PV 230V
DARK LIGHT; 11 OFFICE & KITCHEN



Informacija o izdelku

CCT and Power variable 40W UGR17 Linear system with 48 LED spots and uplight for suspended installation, ideal for offices. Complete with 2 x power variable drivers. Complies with standard EN60598-1 and any other specific standards.

Tehnični podatki

neto dolžina (mm)	1.300,00
neto širina (mm)	35,00
neto višina (mm)	70,00
barva	bela
material	aluminij
kot osvetlitve (°)	34/120
indeks bleščanja (UGR)	<17
krmilna naprava	LED napajalnik
delovna napetost AC (V)	220-240
vhodna napetost AC (V)	220-240
okov	LED Platine
sistemska učinkovitost (lm/W)	95

Tehnični podatki - Nadaljevanje

moč (W)	40 30 20
barva svetlobe	hladno bela toplo bela nevtrarno bela
barvna temperatura (K)	5000 4000 3000
indeks barvnega videza Ra	≥90
svetlobni tok (lm) (lm)	max. 1800/3800
zatemnilno	ne
zaščitni razred	I
stopnja mehanske zaščite	IP20
premer (mm)	68
DxŠxV mm	1300x35x70

Merska skica: 38150BU/W/V bel 48x reflektor 40W 34° UGR17+UPLIGHT 20W 120°



Opis	Šifra
38150BU/W/V bel 48x reflektor 40W 34° UGR17+UPLIGHT 20W 120° direktna (20/30/40W) 34° / indirektna (16/20/25W) 120°, 3m kabla; CCTV PV 230V DARK LIGHT; 11 OFFICE & KITCHEN	LID17788