

Podatkovni list izdelka: LIMQ1E805A

M48 Area QU-D 1 modul 48LEDs 114W 4000K 10775lm IP66 RAL9006

Version with 1 Module 48LEDs - SK.II - Power of luminaire 114W with Lumen output 10.775lm @700mA, Power of luminaire 83W with lumen output 8.615lm @525mA, Power of luminaire 55W with lumen output 6.215lm @350mA - "Economy" Version (ON-OFF)



Tehnični podatki

Vrsta sijalk	Industrijski reflektor za hale
Montaža	Nadgradna stropna Viseča montaža
Barva	RAL 9006 (siva)
Material	Aluminij
Krmilna naprava	LED napajalnik
Delovna napetost AC (V)	230
Svetilno telo	LED
Grlo	LED Platine
Moč (W)	114
Barva svetlobe	navtržno bela
Barvna temperatura (K)	4000
Barvni indeks	≥70
Lumnov (lm)	10775

Tehnični podatki - Nadaljevanje

Število svetilk	1
Zaščitni razred	II
Stopnja zaščite	IP66
S svetlobnim virom	da
DxŠxV mm	495x175x65

Tabela izdelkov

Opis	Šifra
M48 Area QU-D 1 modul 48LEDs 114W 4000K 10775lm IP66 RAL9006 Version with 1 Module 48LEDs - SK.II - Power of luminaire 114W with Lumen output 10.775lm @700mA, Power of luminaire 83W with lumen output 8.615lm @525mA, Power of luminaire 55W with lumen output 6.215lm @350mA - "Economy" Version (ON-OFF)	LIMQ1E805A
Dodatna oprema	
Stropni nosilec za M48 Area, RAL9006	LI06MQ900A
Obešalo z žično vrvjo-komplet za M48 Area kot visečo svetilko, l=1,5m	LI06MQ901J