

Podatkovni list izdelka: LIMQ1L605A

M48 Area QU-D 2modula 96LEDs 227W 4000K 21545lm IP66 RAL9006

Version with 2 Modules 96LEDs - SK.II - Power of luminaire 227W with Lumen output 21.545lm @700mA, Power of luminaire 166W with Lumen output 17.225lm @525mA, Power of luminaire 109W with Lumen output 12.425lm @350mA - "Economy" Version (ON-OFF)



Tehnični podatki

Vrsta sijalk	Industrijski reflektor za hale
Montaža	Nadgradna stropna Viseča montaža
Barva	RAL 9006 (siva)
Material	Aluminij
Krmilna naprava	LED napajalnik
Delovna napetost AC (V)	230
Svetilno telo	LED
Grlo	LED Platine
Moč (W)	227
Barva svetlobe	navtržno bela
Barvna temperatura (K)	4000
Barvni indeks	≥70
Lumnov (lm)	21545

Tehnični podatki - Nadaljevanje

Število svetilk	2
Zaščitni razred	II
Stopnja zaščite	IP66
S svetlobnim virom	da
DxŠxV mm	495x340x65

Tabela izdelkov

Opis	Šifra
M48 Area QU-D 2modula 96LEDs 227W 4000K 21545lm IP66 RAL9006 Version with 2 Modules 96LEDs - SK.II - Power of luminaire 227W with Lumen output 21.545lm @700mA, Power of luminaire 166W with Lumen output 17.225lm @525mA, Power of luminaire 109W with Lumen output 12.425lm @350mA - "Economy" Version (ON-OFF)	LIMQ1L605A
Dodatna oprema	
Stropni nosilec za M48 Area, RAL9006	LI06MQ900A
Obešalo z žično vrvjo-komplet za M48 Area kot visečo svetilko, l=1,5m	LI06MQ901J