

Podatkovni list izdelka: SR3PDIPS06

PDU PRO Switched; 24xCombo (C13, C15, C19, C21); 400V; 32A

fazno merjenje (merjenje na nivoju vtičnice je mogoče nadgraditi z licenco), možnost preklopa za vsako vtičnico, vklj. pritrdilni kotnik z vijaki



SCHRACK-Info

- PDU PRO Switched
- Metering per phase
- Can be upgraded to measuring per socket at any time via licence (SR3PAB0011, SR3PAB0012, SR3PAB0013)
- switchable sockets
- Input: 32 A / 400 V | 22 kW
- Supply cable: 3,0 m | 4 mm²
- with CEE plug 32 A red
- Output: 24x Combo C13/C15/C19/C21
- 6x hydraulic-magnetic circuit breakers 16 A
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display

- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) </l

Tehnični podatki

neto dolžina (mm)	1.710,90
neto širina (mm)	56,00
neto višina (mm)	71,00
EAN-koda	4057298230608
cena	3.886,00
min. temperatura okolja (°C)	0
maks. temperatura okolja (°C)	50
nazivna napetost	400V
stopnja mehanske zaščite	IP20
tip izdelka	Switched
število vtičnic	24
tip vtičnice	24 x Combo Socket (C13/C15/C19/C21)
nazivni tok (A)	32
Phases per feed	3
vrsta priključka	CEE 32 A rdeča
protokol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
vrsta montaže	Bracket (L-shape)

Opis	Šifra
PDU PRO Switched; 24xCombo (C13,C15,C19,C21); 400V; 32A fazno merjenje (merjenje na nivoju vtičnice je mogoče nadgraditi z licenco), možnost preklopa za vsako vtičnico, vklj. pritrdilni kotnik z vijaki	SR3PDIPS06